

Universal Beams

Designation Size (mm)	Mass Per Metre (kg/m)	Depth (mm)	Width (mm)	Web Thickness (mm)	Flange Thickness (mm)
127x76	13.0	127.0	76.0	4.0	7.6
152x89	16.0	152.4	88.7	4.5	7.7
178x102	19.0	177.8	101.2	4.8	7.9
203x102	23.1	203.2	101.8	5.4	9.3
203x133	25.1	203.2	133.2	5.7	7.8
203x133	30.0	206.8	133.9	6.4	9.6
254x102	22.0	254.0	101.6	5.7	6.8
254x102	25.2	257.2	101.9	6.0	8.4
254x102	28.3	260.4	102.2	6.3	10.0
254x146	31.1	251.4	146.1	6.0	8.6
254x146	37.0	256.0	146.4	6.3	10.9
254x146	43.0	259.6	147.3	7.2	12.7
305x102	24.8	305.1	101.6	5.8	7.0
305x102	28.2	308.7	101.8	6.0	8.8
305x102	32.8	312.7	102.4	6.6	10.8
305x127	37.0	304.4	123.4	7.1	10.7
305x127	41.9	307.2	124.3	8.0	12.1
305x127	48.1	311.0	125.3	9.0	14.0
305x165	40.3	303.4	165.0	6.0	10.2
305x165	46.1	306.6	165.7	6.7	11.8
305x165	54.0	310.4	166.9	7.9	13.7
356x127	33.1	349.0	125.4	6.0	8.5
356x127	39.1	353.4	126.0	6.6	10.7
356x171	45.0	351.4	171.1	7.0	9.7
356x171	51.0	355.0	171.5	7.4	11.5
356x171	57.0	358.0	172.2	8.1	13.0
356x171	67.1	363.4	173.2	9.1	15.7
406x140	39.0	398.0	141.8	6.4	8.6
406x140	46.0	403.2	142.2	6.8	11.2
406x178	54.1	402.6	177.7	7.7	10.9
406x178	60.1	406.4	177.9	7.9	12.8
406x178	67.1	409.4	178.8	8.8	14.3
406x178	74.2	412.8	179.5	9.5	16.0